TECHNICAL SPECIFICATION CALEVA MULTI LABSCIENTIFIC (MLS)



MULTI LAB SCIENTIFIC (MLS)

Gain deeper insights into process parameters and accelerate your formulation development with the all-in-one benchtop mixer, extruder and spheronizer from Caleva. With tool-less technology and automatic data capture, you can complete multiple experiments in a day and achieve reliable repeatability across multiple iterations.



- Automatic Data Capture
- Recipe Management
- USB Microscope Imaging

- Ambient & Process Temperature Measurement
- Motor Load % Reporting
- Speed Reporting

Standard Product Configuration (Software – MLS1.01): - 230v 50/60Hz - Part Number: MLX-2SBXU - 110v 50/60Hz - Part Number: MLX-1SBXU Electrical Supply: 1ph 230V or 110V Connectivity: 2 x USB3, 2 x USB2 Base Machine Mass: 34kg Base Machine Dimensions: 505 (W) x 600 (D) x 420 (H) mm Machine Cabinet: Polyurethane and 304 Stainless Steel Product Contact: 316 Stainless Steel and FDA food approved plastics

Mixer Attachment

Processing capacity: 15 to 40q / 30 to 80ml (formulation and bowl dependent).

Blade rotation speed: Primary Blade 10 to 250 RPM

Mixer Bowl: Intermeshing counter rotating blades for high shear applications. Other bowl options include half bowl for scarce materials, sigma bowl for higher viscosity materials and water jacketed options.

Extruder Attachment



Processing capacity: 10 to 80g (formulation dependent). Screw speed: 90 to 150 RPM **Die plate:** One Ø1mm x 1mm supplied as standard. Other die options available: Ø0.5mm to Ø3.0mm holes including lobed profiles and a range of die thicknesses.



Spheronizer Attachment

Processing capacity: 10 to 80g (formulation dependent). Disc Speed: 500 to 4500 RPM Spheronization Disc: One 3x3mm crosshatch serration disc supplied as standard. Other disc patterns are available.

